
## **AUSVINE MACHINERY PTY LTD**

## COLLARD TRIMMER PROFILMATIC® 2200 special Version 4 REF. PARASOL FRAME

- ♦ Vine Trimmer that operates
- 2 half rows at a time
- ◆ **specific frame**. distance between

the 2 vertical cutting element =  $\underline{600mm}$  to  $\underline{2400mm}$ .

- ◆ Equipped with <u>6 hydraulic motors 12cc</u>.
- ♦ WITH anti-shock on lower skirting elements.
- ♦1 Cylinder for width.
- ♦1 Cylinder for general UP/DOWN adjustment 500mm.
- ♦2 Cylinders 500mm for independent UP/DOWN adjustment of the 2 vertical cutting elements.
- ♦ Manual adjustment of the angle for the top cutting elements and the lower cutting elements.



- Each top cutting element = 1.30m (composed of 800mm + 400mm).
- ♦ The 2 tops cutting elements are adjustable in height, manually.
- ♦ Cutting height = 1,30m.
- ♦ Lower skirt elements = 400mm + 400mm.
- ◆1 electric controls distributor equipped with 1SE + 4DE (with filter, limiter for oil & pressure and collector).
- ♦ With **NEW JOYSTICK**.
- ♦ Mast mounting point height to 750mm.
- ♦ With the lower shirting elements to be at 100mm from ground, when at 45° and vertical element at its lowest point.
- ◆ Equipped with **braces**
- ♦ With a **storage support**.